




FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		201X 713H 2000 212		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		201P 713H 2100 213		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/ 6393		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM 4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	On Condition		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL	
SPECIFICATION		HM 4922	
PART NO. / DRAWING NO.		AE/ 6394	
SIZES		As per drawing	
MATERIAL SPECIFICATION		HM 4922	
OPERATING TEMPERATURE		- 55°C to +160°C	
END USE	SYSTEM	Air-conditioning & Ventilation system	
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable	
	LIFE	ON CONDITION	
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007	
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM	
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/ 6395		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/6655		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/7857		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/4345		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/185-AFV 125		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/185-GS2-30 mm		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922, XC-80		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	


FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/185-AFV1-30-2000		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)	

FIRE PROOF SEAL

DESCRIPTION OF THE ITEM		FIRE PROOF SEAL		
SPECIFICATION		HM 4922		
PART NO. / DRAWING NO.		AE/157		
SIZES		As per drawing		
MATERIAL SPECIFICATION		HM4922		
OPERATING TEMPERATURE		- 55°C to +160°C		
END USE	SYSTEM	Air-conditioning & Ventilation system		
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable		
	LIFE	ON CONDITION		
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007		
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM		
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.	
----		RCMA(H/C)/LTCC/55-2/2009 Date: 16.01.2009	TA 1171 (for rubber compound)	

FIRE PROOF DUCT

DESCRIPTION OF THE ITEM		FIRE PROOF DUCT	
SPECIFICATION		HM 4922	
PART NO. / DRAWING NO.		201X 214H 0000 202	
SIZES		As per drawing	
MATERIAL SPECIFICATION		HM4922	
OPERATING TEMPERATURE		- 55°C to +160°C	
END USE	SYSTEM	Air-conditioning & Ventilation system	
	HELICOPTER / AIRCRAFT	Helicopters and other Aircraft wherever suitable	
	LIFE	ON CONDITION	
TEST SCHEDULE / TEST ORDER NO.		QTS/ALH/085 Date: 15.05.2007	
DEVELOPMENT AGENCY		M/s AEROSPACE ENGINEERS, SALEM	
PROVISIONAL CLEARANCE NO. & DATE		LOCAL TYPE CERTIFICATION COMMITTEE APPROVAL NO.	TYPE APPROVAL NO.
----		RCMA(H/C)/LTCC/55-2/2008 Date: 14.01.2008	TA 1171 (for rubber compound)